

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 895 425 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
03.02.1999 Bulletin 1999/05

(51) Int. Cl.⁶: H04N 7/36

(21) Application number: 98114003.1

(22) Date of filing: 27.07.1998

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: Sugiyama, Kenji
Yokosuka-shi, Kanagawa-ken (JP)

(74) Representative:
Leson, Thomas Johannes Alois, Dipl.-Ing. et al
Patentanwälte
Tiedtke-Bühling-Kinne & Partner,
Bavariaring 4
80336 München (DE)


(30) Priority: 28.07.1997 JP 217064/97

(71) Applicant:
Victor Company of Japan, Ltd.
Yokohama 221-0022 (JP)

(54) A motion-compensated coder with motion vector accuracy control

(57) A decoder for decoding video data through motion-compensated prediction coding and a method of motion-compensated-predictive-coding video data are disclosed. N kinds of motion vectors at N different accuracies are obtained every first block of pixels of the video data respectively, the N kinds of motion vectors are combined at every second block including M of the first blocks are every the N different accuracies, M and N being natural numbers more than one, N amounts of code of the N kinds of motion vectors are obtained and motion-compensated-predictive-coded video data are obtained using the N kinds of the motion vectors at every the accuracy; one of the N different accuracies

showing the lowest one of the N amounts is selected; accuracy data indicative of the one of the N different accuracies is generated; the motion vectors corresponding to the selected one of the N different accuracies are outputted; and the video data is motion-compensated-predictive-coded using the outputted motion vectors at the selected one of the N different accuracies, and the motion-compensated-predictive-coded video data, the outputted motion vectors, and the accuracy data are outputted. The corresponding decoder and a corresponding method are also disclosed.



EP 0 895 425 A2

Description

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] This invention relates to a motion-compensated coder, a decoder, a method of motion-compensated coding, and a method of decoding.

2. Description of the Prior Art

[0002] A motion compensated coder for motion-compensated-coding video data is known and a decoder for decoding the motion-compensated-coded video data is also known.

[0003] The motion compensation is generally effected every unit of 16 x 16 pixels to 8 x 8 pixels. The motion of an image, i.e., the motion vector is obtained at the same unit. An accuracy of the motion vector(MV) is generally one or a half pixel. If the motion compensation is used in coding, the motion vector is coded and sent to the decoder side.

[0004] Fig. 7 is a block diagram of a prior art motion-compensated coder.

[0005] Input video data is supplied to a subtractor 2 and to a motion estimator 71 through an input terminal 1. The subtractor 2 subtracts a motion-compensated-predicted signal 10a from the input video data and supplies the difference as a prediction error to a DCT (Discrete Cosine Transform) 3.

[0006] The DCT 3 effects a discrete cosine transforming process at 8 x 8 pixels and supplies the obtained coefficients to a quantizer 4. The quantizer 4 quantizes the coefficients with predetermined step amount and outputs a fixed length coded coefficients to the variable length coder 5 and to an inverse quantizer 9.

[0007] Generally, the quantizing step amount is controlled in accordance with an amount of codes to keep the data rate constant.

[0008] The variable length coder 5 converts coefficients of two dimensional 8 x 8 pixels into one dimensional array through zigzag scanning and codes the coefficients by Huffman coding. This inter-frame prediction error signal is multiplexed with coded motion vectors by a multiplexer 14.

[0009] On the other hand, inverse processes of the DCT 3 and the quantizer 4 are executed by the inverse quantizer 9, an inverse DCT 13 to reproduce the inter-frame prediction error. The reproduced prediction error is added to motion-compensated-predicted signal 10a to provide a reproduced video data which is stored in a video memory 73.

[0010] Reproduced video from the video memory 73 is supplied to the motion estimator 71 and to a motion-compensated predictor 72. The processing from the inverse quantizer 9 to the video memory 73 is called as local decoding which is essentially the same processing

of the corresponding decoder.

[0011] The motion-compensated predictor 72 shifts video data stored in the video memory 73 every block in accordance with the motion vectors from the motion estimator 71 to obtain a motion-compensated-predicted signal 10a which is supplied to the subtractor 2 and to the adder 12.

[0012] The motion estimator 71 effects block matching between the reproduced video data stored in the video memory 73 and the input video data with the reproduced video data shifted every motion compensation block and determines the motion vector MV showing best matching (lowest error). The obtained motion vector is supplied to a motion vector coder 74 for coding the motion vector and to the motion-compensated predictor 72.

[0013] The motion vector coder 74 obtains a difference between horizontal components of the motion vectors at the one block previous block (generally left) and the present block and a difference between vertical components of the motion vectors at the one block previous block (generally left) and the present block and codes the difference values with Huffman codes to supply the obtained code train (bit stream) of the motion vector to the multiplexer 14 which multiplies the code train (bit stream) of the motion vector with the code train (bit stream) of the inter-frame prediction error signal, i.e., the output of the variable length coder 5 to output coded signal 15.

[0014] Fig. 8 is a block diagram of a prior art decoder corresponding to the motion-compensated prediction coder shown in Fig. 7.

[0015] The coded signal 15 is inputted from an input 21 and supplied to a separator 22 which separates the coded signal into the code train of the inter-frame prediction error and the code train of the motion vectors. The inter-frame prediction error is converted into the fixed length code by a variable length decoder 23 which outputs 8 x 8 pixels of coefficients which are supplied to an inverse quantizer 9. The inverse quantizer 9 and an inverse DCT 13 outputs reproduced prediction errors. On the other hand, the code train of the motion vectors is supplied to a motion decoder 81 which decodes the code train of the motion vectors and supplies the obtained motion vector data to a motion-compensated predictor 82. The motion-compensated predictor 82 generates inter-frame prediction signal with the video data stored in a video memory 83 motion-compensated in accordance with the motion vector data from the motion vector decoder 81. The adder 12 adds the inter-frame prediction error signal to the reproduced prediction errors to output reproduced video data 124 which is stored in the video memory 83. The adder 12, the inverse quantizer 9, and the inverse DCT 13 in Fig. 8 have the same structure as those shown in Fig. 7 respectively.

[0016] In these prior art motion-compensated prediction coder and motion-compensated prediction decoder,

the accuracy of the motion vector is fixed. Therefore, in the case of the image showing a low self-correlation (there is a lot of amounts of high frequency component), it is possible to make the prediction error low by the high accuracy motion prediction. However, in the case of the image showing high self-correlation (there is a few amount of high frequency component) the high accuracy motion compensation prediction does not contribute to reduction in the prediction error, so that the motion vector data is not efficiently used.

SUMMARY OF THE INVENTION

[0017] The aim of the present invention is to provide a superior motion-compensated coder, a superior decoder, a superior method of motion-compensated coding and a superior method of decoding.

[0018] According to the present invention, a motion-compensated predictive coding apparatus is provided, which includes: a motion vector estimation circuit responsive to video data and local decoded video data for obtaining N kinds of motion vectors at N different accuracies every first block of pixels of the video data respectively; a vector combining circuit responsive to the motion vector estimation circuit for combining the N kinds of motion vectors at every second block including M of the first blocks every the N different accuracies, M and N being natural numbers, N being more than one; a motion vector accuracy selection circuit responsive to the vector combining circuit, the video data, and the local decoded video data for obtaining N total amounts of code of the N kinds of motion vectors and motion-compensated-predictive-coded video data at the N different accuracies, selecting one of the N different accuracies showing the lowest one of the N total amounts, generating accuracy data indicative of one of the N different accuracies, and outputting the motion vectors corresponding to the selected one of the N different accuracies and the accuracy data; and a motion-compensated predictive coding circuit responsive to the video data and motion vector accuracy selection circuit for motion-compensated-predictive-coding the video data using the outputted motion vectors at the selected one of the N different accuracies, generating the local decoded video data, and outputting the motion-compensated-predictive-coded video data, the outputted motion vectors, and the accuracy data.

[0019] In the motion-compensated predictive coding apparatus, the motion vector accuracy selection circuit may include N first amount detection circuits for coding the motion vectors at every second block and thereby, obtaining the N amounts of code of the N kinds of motion vectors at every N different accuracies; N second amount detection circuits responsive to the video data, the local decoded video data, and the vector combining circuit for motion-compensated-predictive-coding the video data using the N kinds of motion vectors every second block to generate N kinds of prediction error

codes, and obtaining N amounts of the prediction error codes respectively; N adders for respectively adding the N amounts of code of the N kinds of motion vectors to the N kinds of prediction error codes to obtain the N total amounts; and a selection circuit for selecting one of the N different accuracies corresponding to the lowest one of the N total amounts; and an outputting circuit for generating and outputting the accuracy data indicative of the selected one of N different accuracies and selectively outputting the motion vectors corresponding to the selected one of N different accuracies.

[0020] According to the present invention, a decoder supplied with coded data including motion-compensated-predicted video data and data including codes of motion vectors and accuracy data, is provided, the motion vectors being obtained every first block at one of N accuracies every second block including M of the first block at one of the N accuracies indicated by the accuracy data. It includes: a separating circuit for separating the coded data into the motion-compensated-predicted video data and the data; a motion-compensated inter-frame prediction circuit including a multiplying circuit responsive to the separating circuit for generating a motion-compensated inter-frame predicted signal from the codes of motion vectors multiplied with the accuracy data, so that the accuracy is selected every second block; and an inter-frame prediction decoding circuit for decoding the motion-compensated-predicted video data from the separating circuit with the motion-compensated inter-frame prediction signal and outputting decoded video data.

[0021] According to the present invention, a method of motion-compensated-predictive-coding video data is provided. The method includes steps of: (a) obtaining N kinds of motion vectors at N different accuracies every first block of pixels of the video data respectively; (b) combining the N kinds of motion vectors at every second block including M of the first blocks every the N different accuracies, M and N being natural numbers, N being more than one; (c) obtaining N total amounts of code of the N kinds of motion vectors and motion-compensated-predictive-coded video data obtained using the N kinds of the motion vectors at every the accuracy; (d) selecting one of the N different accuracies showing the lowest one of the N amounts; (e) generating accuracy data indicative of selected one of the N different accuracies; (f) outputting the motion vectors corresponding to the selected one of the N different accuracies; (g) motion-compensated-predictive-coding the video data using the outputted motion vectors at the selected one of the N different accuracies, generating the local decoded video data, and (h) outputting the motion-compensated-predictive-coded video data, the outputted motion vectors, and the accuracy data.

[0022] In this method, the step (d) may comprise steps of: coding the motion vectors at every second block at the N different accuracies; obtaining the N amounts of code of the N kinds of motion vectors at every N differ-

ent accuracies; motion-compensated-predictive-coding the video data using the N kinds of motion vectors every second block to generate N kinds of prediction error codes; obtaining N amounts of the N kinds of prediction error codes; respectively adding the N amounts of code of the N kinds of motion vectors to the N kinds of prediction error codes to obtain the N total amounts; and selecting one of the N different accuracies corresponding to the lowest one of the N total amounts; generating accuracy data indicative of one of the N different accuracies showing the lowest one of the N total amounts; and outputting the accuracy data and the motion vectors corresponding to the selected one of the N different accuracies.

[0023] According to the present invention, a method of decoding coded video data including motion-compensated-predicted video data and data including codes of motion vectors and accuracy data is provided, the motion vectors being obtained every first block at one of N accuracies selected every second block including M of the first block at one of the N accuracies indicated by the accuracy data, M and N being natural numbers, N being more than one. The method comprises the steps of: separating the coded video data into the motion-compensated-predicted video data and the data including codes of motion vectors and accuracy data; generating a motion-compensated inter-frame predicted signal from the codes of motion vectors multiplied with the accuracy data, the accuracy being selected every second block; and decoding the separated motion-compensated-predicted video data with the motion-compensated inter-frame predicted signal; and outputting the decoded video data.

BRIEF DESCRIPTION OF THE DRAWINGS

[0024] The object and features of the present invention will become more readily apparent from the following detailed description taken in conjunction with the accompanying drawings in which:

Fig. 1 is a block diagram of a motion-compensated coder of this embodiment of this invention;

Fig. 2 is a block diagram of a decoder for the motion-compensated prediction coder shown in Fig. 1;

Fig. 3 is a block diagram of the motion accuracy selector shown in Fig. 1;

Figs. 4A and 4B are block diagrams of the code amount estimator shown in Fig. 3;

Fig. 5 is an illustration of this embodiment showing motion vector groups;

Figs. 6A to 6C are graphical drawings of this embodiment showing variation of the amount of code;

Fig. 7 is a block diagram of a prior art motion-compensated coder; and

Fig. 8 is a block diagram of a prior art decoder for

the motion-compensated prediction coder shown in Fig. 7.

[0025] The same or corresponding elements or parts are designated with like references throughout the drawings.

DETAILED DESCRIPTION OF THE INVENTION

[0026] Prior to describing embodiment, the concept of this invention will be described.

[0027] In this invention, a total amount of code is reduced by obtaining N (a natural number more than one) kinds of motion vectors at N different accuracies, combining the N kinds of motion vectors into N groups (motion vector blocks) of the motion vectors every the N different accuracies, obtaining N amounts of codes with the N kinds of motion vectors, selecting and outputting one of the N different accuracies showing a lowest amount of the code.

[0028] Then, at the image showing low self-correlation (fine picture image), the accuracy of the motion compensation becomes fine, so that the inter-frame prediction error becomes lowest. At this portion, because the motion is slow, so that the amount of the codes of the motion vectors does not largely increase.

[0029] On the other hand, at the flat image showing high self-correlation, the accuracy of the motion compensation becomes coarse, so that the amount of the codes of the motion vectors decreases. At such image, the accuracy of the motion compensation does not affect the inter-frame prediction error too much. In the case of a quickly moving portion, the self-correlation is also high due to motion blur.

[0030] In this invention, data of the accuracy of the motion compensation is added to the outputted video data. However, it is negligible amount because one or two bits per tens blocks and the total amount of codes is low because the accuracy of the motion vectors which is estimated to be lowest is selected.

[0031] Hereinbelow will be described an embodiment of this invention.

[0032] Fig. 1 is a block diagram of a motion-compensated coder of this embodiment of this invention.

[0033] Input video data is supplied to a subtractor 2 and to a motion estimator 6 through an input terminal 1. The subtractor 2 subtracts a motion-compensated-predicted signal 10a from the input video data and supplies the difference as a prediction error to a DCT (Discrete Cosine Transform) 3.

[0034] The DCT 3 effects the discrete cosine transforming process at 8 x 8 pixels and supplies the obtained coefficients to a quantizer 4. The quantizer 4 quantizes the coefficients with predetermined step amount and outputs a fixed length coded coefficients to the variable length coder 5 and to an inverse quantizer 9.

[0035] Generally, the quantizing step amount is con-

trolled in accordance with an amount of code to keep the data rate constant.

[0036] The variable length coder 5 converts coefficients of two dimensional 8 x 8 pixels into one dimensional array through zigzag scanning and codes the coefficients with Huffman codes.

[0037] On the other hand, inverse processes of the DCT 3 and the quantizer 4 are executed by the inverse quantizer 9, an inverse DCT 13 to reproduce the inter-frame prediction error. The inter-frame prediction error is added to the motion-compensated-predicted signal 10a from a motion-compensated predictor 10 by an adder 12 to provide a reproduced video data which is stored in a video memory 11.

[0038] Reproduced video data from the video memory 11, that is, a local decoded video data 11a is supplied to the motion estimator 6, to the motion-compensated predictor 10, and to a motion vector accuracy selector 8. The processing from the inverse quantizer 9 to the video memory 11 is called as local decoding which is essentially the same processing of a decoder mentioned later.

[0039] The motion-compensated predictor 10 shifts video data stored in the video memory 11 every block in accordance with selected motion vectors from a motion vector accuracy selector 8 to obtain a motion-compensated predicted signal 10a which is supplied to the subtractor 2 and to the adder 12a.

[0040] The motion estimator 6 effects block matching between the reproduced video data stored in the video memory 11 and the input video data with the reproduced video data shifted (shifting a reading address) every motion compensation block and determines the motion vector MV showing best matching (lowest error) every accuracy of motion compensation. The obtained N sets of motion vectors at N accuracies are supplied to a motion vector combiner 7 which combines motion vectors every motion vector group (motion vector block) every accuracy, N being a natural number more than one. The motion accuracy selector 8 obtains total amounts of code of kinds of motion vectors and motion-compensated-predictive-coded video data at the N different accuracies, selects one of the N different accuracies showing the lowest one of the N total amounts, generates accuracy data indicative of the selected one of the N different accuracies, and outputs the motion vectors corresponding to the selected one of the N different accuracies and the accuracy data obtains the total amounts of code of the motion vector and code of prediction errors every accuracy every motion vector group (block) and selects the accuracy of motion compensation showing lowest one of total amounts of codes and supplies the accuracy data and the selected motion vectors to the motion-compensated predictor 10 and to the motion coder 16.

[0041] The coder 16 codes the motion vector data and the accuracy data.

[0042] The motion vector coder 16 obtains a difference between horizontal components of the motion vec-

tors at the one block previous block (generally left) and the present block and a difference between vertical components of the motion vectors at the one block previous block (generally left) and the present block and codes the difference values with Huffman codes to supply the obtained code train of the motion vector to the multiplexer 14.

[0043] The prediction error signal is multiplexed with coded motion vectors and the accuracy data by the multiplexer 14. That is, the multiplexer 14 multiplies the code train of the motion vector and the accuracy data with the code train (bit stream) of the inter-frame prediction error, i.e., the output of the variable length coder 5 to output coded signal.

[0044] The motion estimator 6 obtains motion vectors at different accuracies every motion compensation block. More specifically, the motion vectors is obtained at one pixel accuracy and a half pixel accuracy. A quarter accuracy may be provided.

[0045] The motion vectors at respective accuracies have substantially near values but accuracies are different. Then, it is possible to obtain the low accuracy of motion vectors by rounding the motion vectors at the high accuracy. However, it not always that the prediction error is low when the special distance is small, so that rounding does not provide the most suitable low accuracy motion vectors.

[0046] Particularly, if the accuracies are of one pixel and a half pixel, that is, the accuracy value is twice, rounding may cause offset.

[0047] However, because there is not large difference between the motion vectors at the low accuracy and the high accuracy, it is not disable but possible that the high accuracy motion vector is obtained from the difference from the low accuracy motion vectors.

[0048] The motion vector combiner 7 combines the motion vector every accuracy at every motion vector group.

[0049] Fig. 5 is an illustration of this embodiment showing motion vector groups.

[0050] The motion vector groups (motion vector block) are two dimensionally arranged such as Group of Block (GOB).

[0051] The size of the motion vector group may be 8 x 8 of the motion compensation blocks 51 but in this embodiment vertical 4 X horizontal 16 of motion compensation blocks 51 in consideration of signal processing of the input video data and error correction.

[0052] Fig. 3 is a block diagram of the motion accuracy selector 8 shown in Fig. 1.

[0053] The motion accuracy selector 8 selects one of a plurality of accuracies showing the lowest one of N total amounts of the motion vector and outputs the accuracy data and the motion vector of the selected accuracy. That is, N total amounts of codes of the motion vectors and the prediction error of inter-frame are estimated every motion vector group every accuracy and the accuracy showing the lowest one of N total

amounts of codes is selected and the selected motion vector data corresponding to the selected accuracy and the accuracy data are outputted.

[0054] Motion vector at one-pixel accuracy is supplied to a delay 31, a motion-compensated predictor 331, and a motion coder 361. The delay 31 delays the motion vectors of the one-pixel accuracy and a half-pixel accuracy until end of the judging processing, that is, delays one motion vector group and supplies the delayed motion vector to the switch 32.

[0055] The motion-compensated predictors 331 and 332 have the conventional structure and generates prediction signals from the local decoded video data from the video memory 11 and supplies them to subtractors 341 and 342. the subtractors subtracts the prediction signals from the input video data to supply the prediction error to code amount estimators 351 and 352.

[0056] Figs. 4A and 4B are block diagrams of the code amount estimators shown in Fig. 3.

[0057] The code amount estimator shown in Fig. 4A estimates the amount of code from the amount of prediction errors and the code amount estimator shown in Fig. 4B obtains the amount of codes through actual coding the prediction errors. The code amount estimator shown in Fig. 4A comprises a two-dimensional low pass filter 40 for suppressing high frequency components, an accumulator 41 for accumulating the low-pass-filtered prediction errors every motion vector group to obtain an accumulated amount of prediction errors every group. A code amount conversion table 42 converts the accumulated amount into an estimated amount every motion vector group. The code amount conversion table 42 is statistically obtained in advance and is fixed.

[0058] The code amount estimator shown in Fig. 4B comprises a DCT 43, a quantizer 44, a variable length coder 45, and a code amount calculator 46. The DCT 43, the quantizer 44, and the variable length coder 45 provide the coding process which is the same as that by the DCT 3, the quantizer 4, and the variable length coder 5 to provide the same code train. The code amount calculator 46 calculates the amount of the codes every motion vector group. The obtained amount of codes from the code amount estimator 351 and 352 are supplied to the adders 381 and 382 respectively.

[0059] Motion vector coders 361 and 362 obtain amounts of motion vector codes at one-pixel accuracy and half-pixel accuracy through actual coding processing. That is, the motion vector coder 361 and 362 codes the motion vector by the same process as the motion vector coder 16 shown in Fig. 1. The obtained amount of motion vector from the motion vector coders 361 and 362 are supplied to the code amount estimator 371 and 362, and supplied to the adders 381 and 382 respectively.

[0060] Adder 381 adds the estimated amount of motion-compensated predicted error from the code amount estimator 351 to the detected amount of motion vector codes from the code amount estimator 371 and

supplies the total amount of codes to a comparator 39. Similarly, the adder 382 adds the estimated amount of motion-compensated predicted error from the code amount estimator 352 to the detected amount of motion vector codes from the code amount estimator 372 and supplies the total amount of codes to the comparator 39. The comparator 39 compares the total amounts and selects the accuracy showing the lowest total amount of codes and supplies the accuracy data to the switch 32 and to the motion vector coder 16.

[0061] If the motion vector is obtained at the accuracy of a quarter pixel, the total amount of codes is obtained and supplied to the comparator 39 which compares the total amounts of codes at accuracies of one-pixel, half-pixel, and quarter-pixel and selects the accuracy showing the lowest total amount of codes to control the switch 32 and supplies the accuracy data to the motion vector coder 16.

[0062] Figs. 6A to 6C are graphical drawings of this embodiment showing variation of the amounts of code.

[0063] The inventor discovered the variation of the amount of codes, wherein the total amount of code varies in accordance with correlation and the degree of motion of images.

[0064] In Fig. 6A, in the case of low correlation and low degree of motion, the amount of code of prediction error 102a decreases with increase in the motion vector accuracy (the accuracy 0.25 pixel is higher than the accuracy 1.0 pixel). Similarly, in Figs. 6B and 6C, the amounts of code of prediction error 102b and 102c decrease with increase in the motion vector accuracy. That is, it is always that the amount of code of prediction error decreases with increase in the motion vector accuracy.

[0065] In Fig. 6A, the amount of code of motion vector 103a increases with increase in the motion vector accuracy. Similarly, in Figs. 6B and 6C, the amounts of code of motion vectors 103b and 103c increase with increase in the motion vector accuracy. That is, it is always that the amount of code of motion vectors increases with increase in the motion vector accuracy. Accordingly the total amount of code variation (101a to 101c) varies in accordance with the image picture and the motion. Then, the motion vector accuracy selector 8 adaptively selects the motion vector accuracy 8 in accordance with the total amount of code.

[0066] The motion vectors obtained by the motion accuracy selector 8 is supplied to the motion-compensated predictor 10 and to the motion vector coder 16. In addition, the motion accuracy selector 8 supplies the accuracy data indicative of the selected accuracy of the motion vector to the motion vector coder 16.

[0067] The motion vector coder 16 converts the codes of the motion vectors into a variable length codes. The variable length coding may be the well known variable length coding. However, it is desirable that the variable length coding is performed every motion vector group to effectively code the motion vectors.

[0068] In the motion vector coder 16, because the accuracy data is multiplexed every motion vector group, the values of the motion vectors are normalized as the motion vector code at one pixel accuracy and the common conversion code table is used.

[0069] In Fig. 1, delaying is not specially shown. However, it is necessary to delay the processing of the prediction coding by the interval necessary for processing in the motion vector combiner 7 and the motion accuracy selector 8.

[0070] Fig. 2 is a block diagram of a decoder for the motion-compensated prediction coder shown in Fig. 1.

[0071] The coded data is inputted from an input 21 and supplied to a separator 22 which separates the coded data into the code train of the inter-frame prediction errors supplied to a variable length decoder 23 and the code train of the motion vectors and accuracy data supplied to a motion vector decoder 25. The inter-frame prediction error is converted into the fixed length coder by the variable length decoder 23 and coefficients of 8×8 pixels are supplied to an inverse quantizer 9. The inverse quantizer 9 and an inverse DCT 13b outputs reproduced prediction errors. On the other hand, the code train of the motion vectors is supplied to the motion decoder 25 which decodes the code train of the motion vectors and the accuracy data and supplies the obtained motion vector data, i.e., relative values of motion vector and the accuracy data to a motion vector controller 26. The motion vector controller 26 multiplies the relative values of motion vector by the accuracy data to reproduce the motion vectors and supplies the reproduced motion vectors to a motion-compensated predictor 27. The motion-compensated predictor 27 effects motion compensation to the video data from a video memory 28 in accordance with the motion vector from the motion vector controller 26 and generates and supplies an inter-frame motion-compensated prediction signal to an adder 12. The adder 12 adds the inter-frame motion-compensated signal to the reproduced prediction errors to output reproduced video data 24 which is stored in the video memory 28. The adder 12, the inverse quantizer 9, and the inverse DCT 13 in Fig. 2 have the same structure as those shown in Fig. 1 respectively.

[0072] As mentioned above, in this invention the total amount of codes is reduced by obtaining a plurality of kinds of motion vectors at different accuracies, combining a plurality of kinds of motion vectors into motion vector groups of the motion vectors every accuracy, obtaining amounts of codes every accuracy, selecting one of the different accuracies showing a lowest amount of the code. The motion compensation in coding is effected at different accuracies to reduce the total amount of the code. Inversely, it is assumed that the amount of codes (data rate) is constant, controlling the amount of code makes the quantization fine, so that a quality of the reproduced image is improved.

[0073] As mentioned, the motion-compensated pre-

dictive coding apparatus according to this invention includes, a motion vector estimator 6 responsive to input video data and local decoded video data 11a for obtaining N kinds of motion vectors at N different accuracies every first block (motion compensation block) 51 of pixels of the video data respectively, the vector combiner 7 responsive to the motion vector estimator 6 for combining the N kinds of motion vectors at every second block (motion vector block) 52 including M (4×16) of the first blocks every N different accuracies, M and N being natural numbers, N being more than one, the motion vector accuracy selector 8 responsive to the motion vector combiner 7, the video data, and the local decoded video data 11a for obtaining N amounts of code of the N kinds of motion vectors, selecting one of the N different accuracies showing the lowest total amount of the code, generating accuracy data indicative of one of the N different accuracies, and outputting the motion vectors corresponding to the selected one of the N different accuracies, and a motion-compensated predictive coding circuit 53 responsive to the video data and vector accuracy selector 8 for motion-compensated-predictive-coding the video data using the outputted motion vectors at the selected one of the N different accuracies, generating the local decoded video data, and outputting the motion-compensated-predictive-coded video data, the outputted motion vectors, and the accuracy data.

[0074] A decoder for decoding video data through motion-compensated prediction coding and a method of motion-compensated-predictive-coding video data are disclosed. N kinds of motion vectors at N different accuracies are obtained every first block of pixels of the video data respectively, the N kinds of motion vectors are combined at every second block including M of the first blocks are every the N different accuracies, M and N being natural numbers more than one, N amounts of code of the N kinds of motion vectors are obtained and motion-compensated-predictive-coded video data are obtained using the N kinds of the motion vectors at every the accuracy; one of the N different accuracies showing the lowest one of the N amounts is selected; accuracy data indicative of the one of the N different accuracies is generated; the motion vectors corresponding to the selected one of the N different accuracies are outputted; and the video data is motion-compensated-predictive-coded using the outputted motion vectors at the selected one of the N different accuracies, and the motion-compensated-predictive-coded video data, the outputted motion vectors, and the accuracy data are outputted. The corresponding decoder and a corresponding method are also disclosed.

Claims

1. A motion-compensated predictive coding apparatus comprising:

motion vector estimation means responsive to video data and local decoded video data for obtaining N kinds of motion vectors at N different accuracies every first block of pixels of said video data respectively;

vector combining means responsive to said motion vector estimation means for combining said N kinds of motion vectors at every second block including M of said first blocks every said N different accuracies, M and N being natural numbers, N being more than one;

motion vector accuracy selection means responsive to said vector combining means, said video data, and said local decoded video data for obtaining N total amounts of code of said N kinds of motion vectors and motion-compensated-predictive-coded video data at said N different accuracies, selecting one of said N different accuracies showing the lowest one of said N total amounts, generating accuracy data indicative of the selected one of said N different accuracies, and outputting said motion vectors corresponding to the selected one of said N different accuracies and said accuracy data; and

motion-compensated predictive coding means responsive to said video data and vector accuracy selection means for motion-compensated-predictive-coding said video data using the outputted motion vectors at the selected one of said N different accuracies, generating said local decoded video data, and outputting the motion-compensated-predictive-coded video data, the outputted motion vectors, and the outputted accuracy data.

2. The motion-compensated predictive coding apparatus as claimed in claim 1, wherein said motion vector accuracy selection means comprises:

N first amount detection means for coding said motion vectors at every said second block and thereby, obtaining said N amounts of code of said N kinds of motion vectors at every said N different accuracies;

N second amount detection means responsive to said video data, said local decoded video data, and said vector combining means for motion-compensated-predictive-coding said video data using said N kinds of motion vectors every said second block to generate N kinds of prediction error codes, and obtaining N amounts of said prediction error codes respectively;

N adders for respectively adding said N amounts of code of said N kinds of motion vectors to said N kinds of prediction error codes to obtain said N total amounts; and

selection means for selecting one of said N different accuracies corresponding to the lowest one of said N total amounts; and

outputting means for generating and outputting said accuracy data indicative of the selected one of said N different accuracies and selectively outputting said motion vectors corresponding to the selected one of said N different accuracies.

3. A decoder supplied with coded data including motion-compensated-predicted video data and data including codes of motion vectors and accuracy data, said motion vectors being obtained every first block at one of N accuracies selected every second block including M of said first block at one of said N accuracies indicated by said accuracy data, M and N being natural numbers, N being more than one, comprising:

separating means for separating said coded data into said motion-compensated-predicted video data and said data;

motion-compensated inter-frame prediction means including multiplying means responsive to said separating means for generating a motion-compensated inter-frame predicted signal from said codes of motion vectors multiplied with said accuracy data, so that said accuracy is selected every said second block; and

inter-frame prediction decoding means for decoding said motion-compensated-predicted video data from said separating means with said motion-compensated inter-frame prediction signal and outputting decoded video data.

4. A method of motion-compensated-predictive-coding video data, comprising the steps of:

(a) obtaining N kinds of motion vectors at N different accuracies every first block of pixels of said video data respectively;

(b) combining said N kinds of motion vectors at every second block including M of said first blocks every said N different accuracies, M and N being natural numbers, N being more than one;

(c) obtaining N total amounts of code of said N kinds of motion vectors and motion-compensated-predictive-coded video data obtained using said N kinds of said motion vectors at every said accuracy;

(d) selecting one of said N different accuracies showing the lowest one of said N amounts;

(e) generating accuracy data indicative of said one of said N different accuracies;

(f) outputting said motion vectors correspond-

ing to the selected one of said N different accuracies;

(g) motion-compensated-predictive-coding said video data using the outputted motion vectors at the selected one of said N different accuracies, generating said local decoded video data, and
 (h) outputting the motion-compensated-predictive-coded video data, the outputted motion vectors, and said accuracy data.

5. The method as claimed in claim 4, wherein the step (d) comprising steps of:

coding said motion vectors at every said second block at said N different accuracies;
 obtaining said N amounts of code of said N kinds of motion vectors at every said N different accuracies;
 motion-compensated-predictive-coding said video data using said N kinds of motion vectors every said second block to generate N kinds of prediction error codes;
 obtaining N amounts of said N kinds of prediction error codes;
 respectively adding said N amounts of code of said N kinds of motion vectors to said N kinds of prediction error codes to obtain said N total amounts; and
 selecting one of said N different accuracies corresponding to the lowest one of said N total amounts;
 generating accuracy data indicative of said one of said N different accuracies showing the lowest one of said N total amounts; and
 outputting said accuracy data and the motion vectors corresponding to the selected one of said N different accuracies.

6. A method of decoding coded video data including motion-compensated-predicted video data and data including codes of motion vectors and accuracy data, said motion vectors being obtained every first block at one of N accuracies selected every second block including M of said first block at one of said N accuracies indicted by said accuracy data, M and N being natural numbers, N being more than one, comprising the steps of:

separating said coded video data into said motion-compensated-predicted video data and said data including codes of motion vectors and accuracy data;
 generating a motion-compensated inter-frame predicted signal from said codes of motion vectors multiplied with said accuracy data, said accuracy being selected every said second block; and

decoding the separated motion-compensated-predicted video data with said motion-compensated inter-frame predicted signal; and
 outputting said decoded video data.

7. In a high efficient coding apparatus for a moving picture image effecting motion compensation inter-frame prediction to an input motion picture image signal,

motion compensation coding apparatus characterized by comprising:
 motion prediction means for obtaining a plurality of kinds of motion vectors having different accuracies every block;
 motion vector combining means for combining motion vectors of respective said blocks every accuracies and obtaining vector groups every said accuracy;
 motion vector accuracy selection means for selecting one of the accuracies of the motion vectors which is predicted to have a fewer amount of code during coding with motion vectors of respective accuracies every motion vector group; and
 means for effecting motion compensated inter-frame predicted coding using the selected motion vectors.

8. In the motion compensation coding apparatus as claimed in claim 1,

said motion vector selection means comprises:
 means for coding the motion vectors in the motion vector group at respective accuracies and obtaining the amount of the code;
 means for effecting inter-frame prediction with compensation by motion vectors at the motion vector group at respective accuracies and obtaining an amount of code from the obtained prediction errors; and
 means for selecting one of the accuracies of the motion vectors showing a fewer amount in the sum of the amount of code of motion vectors and the amount of code of the prediction errors at respective accuracies every motion vector group.

9. In a high efficient decoding apparatus for a moving picture image effecting motion compensation,

separation means for separating accuracy information every motion vector group unit;
 motion compensation prediction means for obtaining a motion compensation inter-frame predicted signal with the accuracy of the motion vector changed in accordance with the accuracy information of said motion vector

every motion vector group unit; and
means for obtaining a reproduction image
through inter-frame prediction decoding with
said motion compensation inter-frame pre-
dicted signal.

5

10. In a method of high efficient coding for a moving
picture image effecting motion compensation inter-
frame prediction to an input motion picture image
signal,

10

a method of motion compensation coding char-
acterized by the steps of:
obtaining a plurality of kinds of motion vectors
having different accuracies every block; combin-
ing motion vectors of respective said blocks
every accuracies and obtaining vector groups
every said accuracy; selecting one of the accu-
racies of the motion vectors which is predicted
to have a fewer amount of code during coding
with motion vectors of respective accuracies
every motion vector group; and effecting
motion compensated inter-frame predicted
coding using the selected motion vectors.

15

20

25

11. In the method of motion compensation coding as
claimed in claim 10,

selecting every said motion vector group unit is
effected by coding the motion vectors in the
motion vector group at respective accuracies
and obtaining the amount of the code; effecting
inter-frame prediction with compensation by
motion vectors at the motion vector group at
respective accuracies and obtaining an amount
of code from the obtained prediction errors;
and selecting one of the accuracies of the
motion vectors showing a fewer amount in the
sum of the amount of code of motion vectors
and the amount of code of the prediction errors
at respective accuracies every motion vector
group.

30

35

40


12. In a method of high efficient decoding for a moving
picture image effecting motion compensation char-
acterized by the steps of: separating accuracy infor-
mation every motion vector group unit; obtaining a
motion compensation inter-frame predicted signal
with the accuracy of the motion vector changed in
accordance with the accuracy information of said
motion vector every motion vector group unit; and
obtaining a reproduction image through inter-frame
prediction decoding with said motion compensation
inter-frame predicted signal.

45

50

55

33



F16.2







FIG. 3






F 16.5

51 / 52


ONE PIXEL ACC	ONE PIXEL ACC
ONE PIXEL ACC	HALF PIXEL ACC
HALF PIXEL ACC	HALF PIXEL ACC
HALF PIXEL ACC	QUATER PIXEL ACC
QUATER PIXEL ACC	QUATER PIXEL ACC

51 MOTION COMPENSATION
BLOCK




52
— MOTION VECTOR
BLOCK

FIG. 6A




LOW CORRELATION AND
LOW DEGREE OF
MOTION

FIG. 6B



INTERMEDIATE CORRELATION
AND INTERMEDIATE DEGREE
OF MOTION

FIG. 6C



HIGH CORRELATION
AND HIGH DEGREE
OF MOTION

FIG. 7 PRIOR ART






FIG. 8 PRIOR ART





Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 895 425 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
28.03.2001 Bulletin 2001/13

(51) Int. Cl.⁷: H04N 7/36, H04N 7/26

(43) Date of publication A2:
03.02.1999 Bulletin 1999/05

(21) Application number: 98114003.1

(22) Date of filing: 27.07.1998

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: Sugiyama, Kenji
Yokosuka-shi, Kanagawa-ken (JP)

(30) Priority: 28.07.1997 JP 21706497

(74) Representative:
Leson, Thomas Johannes Alois, Dipl.-Ing. et al
Patentanwälte
Tiedtke-Bühling-Kinne & Partner,
Bavariaring 4
80336 München (DE)


(71) Applicant:
Victor Company of Japan, Ltd.
Yokohama 221-0022 (JP)

(54) A motion-compensated coder with motion vector accuracy control

(57) A decoder for decoding video data through motion-compensated prediction coding and a method of motion-compensated-predictive-coding video data are disclosed. N kinds of motion vectors at N different accuracies are obtained every first block of pixels of the video data respectively, the N kinds of motion vectors are combined at every second block including M of the first blocks are every the N different accuracies, M and N being natural numbers more than one, N amounts of code of the N kinds of motion vectors are obtained and motion-compensated-predictive-coded video data are obtained using the N kinds of the motion vectors at every the accuracy; one of the N different accuracies

showing the lowest one of the N amounts is selected; accuracy data indicative of the one of the N different accuracies is generated; the motion vectors corresponding to the selected one of the N different accuracies are outputted; and the video data is motion-compensated-predictive-coded using the outputted motion vectors at the selected one of the N different accuracies, and the motion-compensated-predictive-coded video data, the outputted motion vectors, and the accuracy data are outputted. The corresponding decoder and a corresponding method are also disclosed.

FIG. 3





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 11 4003

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	SIU-LEONG IU: "COMPARISON OF MOTION COMPENSATION USING DIFFERENT DEGREES OF SUB-PIXEL ACCURACY FOR INTERFIELD/INTERFRAME HYBRID CODING OF HDTV IMAGE SEQUENCES" PROCEEDINGS OF THE INTERNATIONAL CONFERENCE ON ACOUSTICS, SPEECH AND SIGNAL PROCESSING (ICASSP), US, NEW YORK, IEEE, vol. CONF. 17, 23 March 1992 (1992-03-23), pages 465-468, XP000378969 ISBN: 0-7803-0532-9 * the whole document *	1-12	H04N7/36 H04N7/26
A	US 5 576 767 A (LEE CHONG U ET AL) 19 November 1996 (1996-11-19) * column 2, line 33 - column 3, line 18 * * column 8, line 4 - column 9, line 58 *	1-12	
A	US 5 477 272 A (ZAFAR SOHAIL ET AL) 19 December 1995 (1995-12-19) * abstract * * column 5, line 13 - column 8, line 41 *	1-12	
A	US 5 311 310 A (WATANABE HIROSHI ET AL) 10 May 1994 (1994-05-10) * column 1, line 19 - column 3, line 22 *	1-12	TECHNICAL FIELDS SEARCHED (Int.Cl.6) H04N
A	EP 0 765 088 A (TEKTRONIX INC) 26 March 1997 (1997-03-26) * abstract *	1-12	
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 1 February 2001	Examiner Ibruegger, J
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03/02 (P04001)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 11 4003

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

01-02-2001

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5576767	A	19-11-1996	AU 6099594 A	29-08-1994
			WO 9418799 A	18-08-1994
US 5477272	A	19-12-1995	NONE	
US 5311310	A	10-05-1994	JP 2549479 B	30-10-1996
			JP 6217290 A	05-08-1994
EP 0765088	A	26-03-1997	US 5623313 A	22-04-1997

EPO FORM P0089

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

THIS PAGE BLANK (USPTO)



P.B. 5818 - Patentlaan 2
2280 HV Rijswijk (ZH)
☎ +31 70 340 2040
TX 31651 epo nl
FAX +31 70 340 3016

Europäisches
Patentamt

European
Patent Office

Office européen
des brevets

Zweigstelle
in Den Haag

Branch at
The Hague

Département à
La Haye

JENKENS & GILCHRIST, P.C.
Attn. Mr. Richard J. Moura
1445 Ross Avenue, Suite 3200
DALLAS, Texas 75202-2799
UNITED STATES OF AMERICA

Aktenzeichen/File No./No. du Dossier RS 107121 US
Datum/Date 06.11.01

INTELLECTUAL PROPERTY

NOV 08 2001

JENKENS & GILCHRIST

Das Europäische Patentamt übermittelt hiermit den Standardrecherchenbericht zu dem unten bezeichneten Antrag; Kopien der im Recherchenbericht angeführten Schriften werden in der Anlage beigelegt.

The European Patent Office herewith transmits the Standard Search Report relating to the request indicated below; copies of the documents cited in the search report are enclosed.

L'Office Européen des Brevets à l'honneur de vous transmettre ci-joint le Rapport de Recherche concernant la demande désignée ci-dessous; des copies des documents cités sont jointes.

Zeichen und Datum des Antrages Applicant's reference and date Références et date de la demande	34645-00507 - 280601
Dokument, Gegenstand der Recherche Document subject of the search Objet de la recherche	USA 818043
Einreichungstag Filing date Date de dépôt	26/03/2001
Beanspruchte Priorität Priority claimed Priorité revendiquée	

* DOCKETED
Int. 11-8-01
Action Complete Date: 11-6
EPO Search

OFFICE EUROPÉEN DES BREVETS
Pour le Vice-Président,

R. de Best

THIS PAGE BLANK (USPTO)